

Safety Data Sheet dated 13/1/2012, version 1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Mixture identification: LUBRIFICANTE PER ASTE 75 ML
Trade name: A06199
Trade code:

1.2 Relevant identified uses of the substance/mixture and uses advised against

Recommended use:
PROFESSIONAL LUBRICANT

1.3 Details of the supplier of the safety data sheet

Company:
STAC PLASTIC SPRAY S.R.L. Via E. De Nicola 9/11 10036 Settimo Torinese (To) Italia.
STAC PLASTIC SPRAY S.R.L. Tel. n. +39 011 8977566 Fax n. +39 011 8977491

Competent person responsible for the safety data sheet:
Montini Vittorino stacplas@stacplastic.com

1.4 Emergency telephone number

STAC PLASTIC SPRAY S.R.L. Tel. n. +39 011 8977566 Fax n. +39 011 8977491

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

F+ Extremely flammable
Xi Irritant
N Dangerous for the environment

R Phrases:

R12 Extremely flammable.
R38 Irritating to skin.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Adverse physicochemical, human health and environmental effects:
No other hazards

2.2 Label elements



Xi F+ N Symbols:

Xi Irritant
F+ Extremely flammable
N Dangerous for the environment

R Phrases:

R12 Extremely flammable.
R38 Irritating to skin.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

S Phrases:

S16 Keep away from sources of ignition - No smoking.
S2 Keep out of reach of children.
S23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
S46 If swallowed, seek medical advice immediately and show this container or label.
S51 Use only in well-ventilated areas.
S9 Keep container in a well-ventilated place.

Special Provisions:

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of reach of children.

2.3 Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

Safety Data Sheet
LUBRIFICANTE PER ASTE 75 ML

3.1 Substances


N.A.


3.2 Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

40% - 50% Naphtha (petroleum) hydrotreated heavy
REACH No.: 01-2119463258-33, CAS: 64742-48-9, EC: 919-857-5

Xn; R67-10-65-66

 2.6/3 Flam. Liq. 3 H226


 3.10/1 Asp. Tox. 1 H304


 3.8/3 STOT SE 3 H336


40% - 50% heptane; n-heptane;


Index number: 601-008-00-2, CAS: 142-82-5, EC: 205-563-8


F,Xn,Xi,N; R11-38-50/53-65-67


 2.6/2 Flam. Liq. 2 H225

 3.10/1 Asp. Tox. 1 H304

 3.2/2 Skin Irrit. 2 H315

 3.8/3 STOT SE 3 H336

 4.1/A1 Aquatic Acute 1 H400

 4.1/C1 Aquatic Chronic 1 H410

4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2 Most important symptoms and effects, both acute and delayed

None

4.3 Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2 Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3 Advice for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.

- 6.2 Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3 Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4 Reference to other sections
See also section 8 and 13

7. HANDLING AND STORAGE

- 7.1 Precautions for safe handling:
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2 Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3 Specific end use(s)
None in particular

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters
heptane; n-heptane; - CAS: 142-82-5
VLE 8h: 2085 mg/m³ - 500 ppm
TLV TWA: 400 ppm - 1639,26 mg/m³
TLV STEL: 500 ppm - 2049,08 mg/m³
- DNEL Exposure Limit Values
N.A.
- PNEC Exposure Limit Values
N.A.
- 8.2 Exposure controls
- Eye protection:
Not needed for normal use. Anyway, operate according good working practices.
- Protection for skin:
No special precaution must be adopted for normal use.
- Protection for hands:
Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
- Respiratory protection:
Use adequate protective respiratory equipment, e.g. CEN/FFP-2 or CEN/FFP-3.
- Thermal Hazards:
None
- Environmental exposure controls:
None

9. PHYSICAL AND CHEMICAL PROPERTIES

- 9.1 Information on basic physical and chemical properties
- | | |
|---|---|
| Appearance and colour: | Opalescent light yellow liquid of solvent |
| Odour: | N.A. |
| Odour threshold: | N.A. |
| pH: | N.A. |
| Melting point / freezing point: | N.A. |
| Initial boiling point and boiling range: | N.A. |
| Solid/gas flammability: | N.A. |
| Upper/lower flammability or explosive limits: | N.A. |
| Vapour density: | > 1 |
| Flash point: | < 0 ° C |
| Evaporation rate: | N.A. |
| Vapour pressure: | N.A. |
| Relative density: | 0,75 kg/l |
| Solubility in water: | undissolvable |
| Lipid solubility: | complete |

Safety Data Sheet
LUBRIFICANTE PER ASTE 75 ML

Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Viscosity: N.A.
Explosive properties: N.A.
Oxidizing properties: N.A.

9.2 Other information

Miscibility: N.A.
Fat Solubility: N.A.
Conductivity: N.A.
Substance Groups relevant properties N.A.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

None

10.4 Conditions to avoid:

Stable under normal conditions.

10.5 Incompatible materials:

Avoid contact with combustible materials. The product could catch fire.

10.6 Hazardous decomposition products:

None.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Adopt good working practices, so that the product is not released into the environment.
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

None

N.A.

12.3 Bioaccumulative potential

N.A.

12.4 Mobility in soil

N.A.

12.5 Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6 Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

14.1 UN number:

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

ADR-Class:

IATA-Class:

IMDG-Class:

2.5°F CAP. 2.2.2.1.6 UN1950

3.1

2 Aerosols UN 1950

14.4 Packing Group:

- 14.5 Environmental hazards
Marine pollutant: Marine pollutant
- 14.6 Special Precautions for User
IMDG-Page: 2102
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n. 1272/2008 (CLP), Regulation (CE) n. 790/2009 (1° ATP CLP), Regulation (EU) n. 453/2010 (Annex I).

Where applicable, refer to the following regulatory provisions :

- Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.
- Regulation (EC) nr 648/2004 (detergents).
- 1999/13/EC (VOC directive)

- 15.2 Chemical Safety Assessment
No

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

- R10 Flammable.
- R11 Highly flammable.
- R38 Irritating to skin.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
- CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.
It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.
This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.

Safety Data Sheet
LUBRIFICANTE PER ASTE 75 ML

STOT:
TLV:
TWATLV:
WGK:

Specific Target Organ Toxicity.
Threshold Limiting Value.
Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
German Water Hazard Class.